SDS(Safety Data Sheet)

Product	Kixx MX5 2T FB		
MSDS Number	List No.	Issuing date	Last revised date
-	LB2669	2012-11-30	2024-06-27

1. IDENTIFICATION

1) Product name

Kixx MX5 2T FB

2) Recommended use of the chemical and restriction on use

- Recommended use: Lubricants; 2 stroke motorcycle engine oil
- Restrictions on use: Do not use for any other purpose.

3) Details of the supplier of the safety data sheet

○ **Manufacturer**

- Company name: GS Caltex Corporation
- Address: GS Tower, 508, Nonhyeon-ro, Gangnam-gu, Seoul, Korea
- Emergency telephone number: +82-1899-5145

2. HAZARDS IDENTIFICATION

1) Classification of the product

- Not applicable

2) Label elements

○ **Hazard pictograms**

- Not applicable

○ **Signal word**

- Not applicable

○ **Hazard statements**

- Not applicable

○ **Precautionary statements**

1) Prevention

- Not applicable

2) Response

- Not applicable

3) Storage

- Not applicable

4) Disposal

- Not applicable

3) Other hazards

○ **Product NFPA Level**

(※ 0-Lack, 1-Low, 2-Moderate, 3-High, 4-Very High)

Product name	Health	Flammable	Reaction
Kixx MX5 2T FB	0	1	0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	Trade names and Synonyms	CAS No.	EC No.	Contain Ratio(%)
Distillates (petroleum), hydrotreated heavy paraffinic	Emulsifiable oil	64742-54-7	265-157-1	83 ~ 93
Kerosine	Kerosine (petroleum)	8008-20-6	232-366-4	3 ~ 13
Polyisobutylene		9003-27-4		0.9 ~ 4
Trade secret				1 ~ 5
Distillates (petroleum), solvent-dewaxed light paraffinic		64742-56-9	265-159-2	0.1 ~ 0.3

※ Except for the above components, all components are not listed as they do not meet the criteria for hazardous risk classification in Article 104 (Classification of Hazardous Factors) of Regulated Acts and Occupational Safety and Health Act.

4. FIRST AID MEASURES

1) Eye contact

- In case of contact with material, immediately flush eyes with running water for at least 15 minutes.
- If eye irritation persists: Get medical advice/attention.

2) Skin contact

- In case of contact with material, immediately flush skin with running water for at least 15 minutes.
- Remove and isolate contaminated clothing and shoes.
- Launder contaminated clothing and shoes before re-use.
- If skin irritation occurs: Get medical advice/attention.

3) Inhalation

- Move victim to fresh air.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

4) Ingestion

- If unconscious but breathing, never give anything by mouth
- If swallowed do not induce vomiting, seek medical advice immediat.
- Get immediate medical advice/attention.
- Rinse mouth.

5) Indication of any

- Ensure that medical personnel are aware of the material(s) involved and take

immediate medical attention and special treatment needed	precautions to protect themselves.

5. FIRE FIGHTING MEASURES

1) Suitable (and unsuitable) extinguishing media	- Small fire: Dry sand, dry chemical, alcohol-resistant foam, water spray, regular foam, CO2 (Suitable extinguishing media) - Large fire: Water spray/fog, regular foam (Suitable extinguishing media) - High-pressure water (Unsuitable extinguishing media)
2) Special hazards arising from the substance or mixture	- May be ignited by heat, sparks or flames. - Fire may produce irritating and/or toxic gases. - May cause toxic effects if inhaled.
3) Special protective equipment and precautions for firefighters	- Substance may be transported hot. - Runoff may cause pollution. - Contact may cause burns to skin and eyes. - Dike fire-control water for later disposal; do not scatter the material. - Move containers from fire area if you can do it without risk. - Fire involving Tanks: Cool containers with flooding quantities of water until well after fire is out. - Fire involving Tanks: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. - Fire involving Tanks: ALWAYS stay away from tanks engulfed in fire.

6. ACCIDENTAL RELEASE MEASURES

1) Health considerations and protective equipment	- Do not touch or walk through spilled material. - ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). - Ventilate the contaminated area. - Stop leak if you can do it without risk. - Prevent dust cloud. - Please note that materials and conditions to be avoided.
2) Environmental precautions	- Prevent entry into waterways, sewers, basements or confined areas.
3) Methods and material for containment and cleaning up	- Small Spill: Flush area with flooding quantities of water. - Large Spill: Dike far ahead of liquid spill for later disposal. - With clean shovel place material into clean, dry container and cover loosely; move containers from spill area. - Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. - Small Spill: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

7. HANDLING AND STORAGE

1) Precautions for safe handling

- Wash ... thoroughly after handling.
- Please note that materials and conditions to be avoided.
- Handling refer to engineering control/personal protection section.
- Cuation: High temperature

2) Conditions for safe storage (including any incompatibilities)

- Store in a dry place. Store in a closed container.
- Please note that materials and conditions to be avoided.
- Store in a closed container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

1) Control parameters

Chemical name	Exposure limits	ACGIH TLV	OSHA PEL	Biological limit values(BLV)
Distillates (petroleum), hydrotreated heavy paraffinic	TWA : 0.8 mg/m3	TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)	Not available	Not available
Kerosine	TWA : 200 mg/m3	TWA, 200 mg/m3, Total hydrocarbon vapor Skin	Not available	Not available
Polyisobutylene	Not available	Not available	Not available	Not available
Trade secret	Not available	Not available	Not available	Not available
Distillates (petroleum), solvent-dewaxed light paraffinic	TWA : 0.8 mg/m3	TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)	Not available	Not available

2) Appropriate engineering controls

- Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.
- Adjust the ventilation rate to suit the condition.

3) Personal protection equipment

○ **Respiratory protection**

- Wear a adequate respiratory protection equipment with certificate by considering physicochemical properties of exposured particulate material.
- In case exposured to particulate material, the respiratory protective equipments as follow are recommended. - facepiece filtering respirator or air-putifying respirator,

high-efficiency particulate air(HEPA) filter media or resporator equipped with power
- In lack of oxigan(<19.6%), wear the supplied-air respiratior or self-contained breathing apparatus.
- Consider the warning characteristics beforehand.

○ **Eye protection**
- Wear breathable safety goggles to protect from material causing eye irritation or other disorder.
- An eye wash unit and safety shower station should be available nearby work place.
- In case of direct exposure or potential exposure to the substance, wear safety glasses for chemicals approved in the country.

○ **Hand protection**
- Wear appropriate protective gloves by considering physical and chemical properties of chemicals.
- In case of direct exposure or potential exposure to the substance, wear safety gloves for chemicals approved in the country.

○ **Body protection**
- Wear appropriate protective clothing by considering physical and chemical properties of chemicals.
- In case of direct exposure or potential exposure to the substance, wear protective clothing for chemicals approved in the country.

9. PHYSICAL AND CHEMICAL PROPERTIES

Item	Input Value
Apperance	Liquid
Color	Light blue
Smell	a specific smell of hydrocarbon
Smell Threshold	No Data
pH (Numerical value)	No Data
Melting/Freezing Point	No Data
Boilling Point	No Data
Flash Point	120 ℃
Evaporating Rate	No Data
Flammability(Solid, Gas)	No Data
Explosibility Range	No Data
Steam Pressure	No Data
Solubility	No Data
Vapor Density	No Data
Specific Gravity	0.862
Distribution Coefficient	No Data

SelfIgnition Temperature	No Data
Pyrolysis Temperature	No Data
Viscosity	7.2 mm2/s (at 100℃)
Molecular Weight	No Data

10. STABILITY AND REACTIVITY

1) Chemical Stability and hazardous reactivity
- Stable under normal temperatures and pressures.
- Containers may explode when heated.
- Some may burn but none ignite readily.

2) Conditions to avoid
- Ignition source(heat, spark, flame)

3) Incompatible materials
- Combustibles
- Irritating and/or toxic gas

4) Hazardous decomposition products
- Not available

11. TOXICOLOGICAL INFORMATION

1) Information on the likely routes of exposures

○ **Inhalation**

- No inhalation effects through respiratory system.

○ **Skin contact**

- No effect on skin contact.

○ **Eye contact**

- No effect on eye contact.

○ **Ingestion**

- No ingestion effect through mouth.

2) Health hazard information

○ **Acute toxicity**

*** Oral - Not classified (ATEmix > 2000 mg/kg)**

- Distillates (petroleum), hydrotreated heavy paraffinic : rat(male/female), LD50 > 5,000 mg/kg bw, no deaths (read-across: 64742-56-9) (OECD TG 401, GLP)(ECHA)
- Kerosine : rat(male/female); LD50 > 5000 mg/kg bw, no deaths (OECD TG 420, GLP) (read across: 68333-23-3) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : rat; LD50 > 5000 mg/kg bw, no deaths (OECD TG 401, GLP) (ECHA)

*** Dermal - Not classified (ATEmix > 2000 mg/kg)**

- Distillates (petroleum), hydrotreated heavy paraffinic : rabbit(male/female), LD50 > 5,000 mg/kg bw, no deaths (read-across: 64742-56-9) (OECD TG 402, GLP)(ECHA)

- Kerosine : rabbit(male/female); LD50 > 2000 mg/kg bw, no deaths (OECD TG 402, GLP) (read across: 68333-23-3) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : rabbit; LD50 > 5000 mg/kg bw, no deaths (OECD TG 402, GLP) (ECHA)

*** Inhalation(Gas) - Not applicable**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

*** Inhalation(Vapour) - Not classified (ATEmix > 20 mg/L)**

- Distillates (petroleum), hydrotreated heavy paraffinic : rat(male/female), LC50 > 5.53 mg/L air /4h No deaths (read-across: MRD-87-102) (OECD TG 403)(ECHA)
- Kerosine : rat(male/female); inhalation: vapour; LC50 > 5.28 mg/L air /4h, no deaths (OECD TG 403, GLP) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not available

*** Inhalation(Dust, mist) - Not classified (ATEmix > 5 mg/L)**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not available
- Kerosine : Not available
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : rat; inhalation: aerosol; LC50 > 5.53 mg/L air/4h, no deaths (OECD TG 403) (read across : MRD-87-102) (ECHA)

○ Skin corrosion/Irritation : Not classified

- Distillates (petroleum), hydrotreated heavy paraffinic	:	Solvent dewaxed light paraffinic oil is not considered to be irritating to the skin of rabbits. (read across : 64742-56-9) (GLP)(ECHA)
- Kerosine	:	rabbit; irritating (GLP) (read across: Kerosine/heating oil (F-76-01)) ECHA)
- Polyisobutylene	:	Not available
- Trade secret	:	Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic	:	rabbit; not irritating (GLP) (ECHA)

○ Serious eye damage/irritation : Not classified

- Distillates (petroleum), hydrotreated heavy paraffinic	:	Solvent dewaxed light paraffinic oil is not considered to be an ocular irritant. (read-aross: 64742-56-9) (OECD TG 405, GLP)(ECHA)
- Kerosine	:	rabbit; not irritating (EPA OTS 798.4500, GLP) (read across: 68333-23-3) (ECHA)
- Polyisobutylene	:	Not available
- Trade secret	:	Not available

- Distillates (petroleum), solvent-dewaxed light paraffinic : rabbit; not irritating (GLP) (ECHA)

○ **Respiratory sensitization : Not classified**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not available
- Kerosine : Not available
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not available

○ **Skin sensitization : Not classified**

- Distillates (petroleum), hydrotreated heavy paraffinic : Under the conditions of the test, Solvent dewaxed light paraffinic oil is considered non-sensitizing. (read-aross: 64742-56-9) (OECD TG 406, GLP)(ECHA)
- Kerosine : guinea pig; not sensitising (OECD TG 406, GLP) (read across: 68333-23-3) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : guinea pig; not sensitising (OECD TG 406, GLP) (ECHA)

○ **Carcinogenicity : Not classified**

- Distillates (petroleum), hydrotreated heavy paraffinic : EU CLP 1272/2008 : Carc. 1B (Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346)
- Kerosine : ACGIH : A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
- Polyisobutylene : IARC, EU CLP 1272/2008, OSHA, ACGIH, US EPA IRIS, NTP : not listed
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : EU CLP 1272/2008 : Carc. 1B (Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346)

○ **Germ cell mutagenicity : Not classified**

- Distillates (petroleum), hydrotreated heavy paraffinic : In vitro(CHO cell) Chromosome Aberration Test: negative (read-aross : 64742-53-6) (OECD TG 473, GLP)
  In vivo (mouse micronucleus assay) : negative (read-across : SDPO = solvent-extracted, dewaxed paraffin oil) (OECD TG 474)(ECHA)
- Kerosine : In Vitro Bacterial Reverse Mutation Assay : negative (OECD TG 471) (ECHA), In Vitro Sister Chromatid Exchange Assay in Mammalian Cells : negative (OECD TG 479, GLP) (read across: 64742-81-0) (ECHA)
  In vivo Rodent Dominant Lethal Test : negative (OECD TG 478) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available

- Distillates (petroleum), solvent-dewaxed light paraffinic : in vitro; Mammalian Chromosome Aberration Test : Negative (OECD TG 473, GLP) (ECHA)
in vitro; Mammalian Cell Gene Mutation Test : Positive (OECD TG 476) (ECHA)
in vitro; Bacterial Reverse Mutation Assay : Positive (OECD TG 471, GLP) (ECHA)
in vivo; Mammalian Erythrocyte Micronucleus Test : Negative (OECD TG 474) (ECHA)

○ Reproductive toxicity : Not classified

- Distillates (petroleum), hydrotreated heavy paraffinic : Reproductive performance was not adversely affected at any dose level evaluated. There were no neonatal toxicity observed at any dose level. There were no differences in terms of systemic toxicity between either of the dose formulations. (read-aross : Chevron 100 Neutral) (OECD TG 421, GLP)(ECHA)
- Kerosine : rat(male/female); One-Generation Reproduction Toxicity Study; The reproduction NOAEL was 3000 and 1500 mg/kg/day in males and females, respectively. (the hightest tested) (OECD TG 415, GLP) (read across: JP-8 jet fuel) (ECHA)
rat; 500, 1000, 1500, or 2000 mg/kg/day; It can be concluded that the test substance is not toxic to development. (OECD TG 414) (read across: JP-8 jet fuel) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : rat; Does not adversely affect reproductive function (OECD TG 421, GLP)
rat; Not toxic to offspring and parents (OECD TG 414) (ECHA)

○ Specific target organ toxicity (single exposure) : Not classified

- Distillates (petroleum), hydrotreated heavy paraffinic : Hydronephrosis of the right kidney was observed in one rat but was not considered treatment-related by the study authors. No other abnormalities were observed in any male or female rats. (read-across: 64742-56-9) (OECD TG 401, GLP)(ECHA)
Dermal administration of API 78-9 at 5000 mg/kg did not result in any dermal irritation or signs of clinical toxicity. Gross necroscopy did not reveal any signs of systemic toxicity at the 5000 mg/kg dose level. (read-across: 64742-56-9) (OECD TG 402, GLP)(ECHA)
- Kerosine : oral; rat(male/female); All of the study animals exhibited one or more of the following clinical signs: nasal discharge, ocular discharge, abnormal stools, lethargy, stained coat, and alopecia. LD50 > 5000 mg/kg bw, no deaths (OECD TG 420, GLP) (read across: 68333-23-3) (ECHA)
dermal; rabbit(male/female); At necropsy, dermal irritation at the test site was the only abnormal observation. LD50 > 2000 mg/kg bw, no deaths (OECD TG 402, GLP) (read across: 68333-23-3) (ECHA)
inhalation: vapour; rat(male/female); no significant histological alternations were seen. LC50 > 5.28 mg/L air /4h, no deaths (OECD TG 403, GLP) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : oral; rat; No clinical signs of toxicity observed in either male or female rats. LD50 > 5000 mg/kg bw, no deaths (OECD TG 401, GLP) (ECHA)
dermal; rabbit; No visible signs of clinical toxicity were observed. LD50 > 5000

mg/kg bw, no deaths (OECD TG 402, GLP) (ECHA)

○ **Specific target organ toxicity (repeated exposure) : Not classified**

- Distillates (petroleum), hydrotreated heavy paraffinic : The systemic toxicity NOAEL for this 28-day dermal toxicity study in the rabbit is 1,000 mg/kg, based on the lack of adverse systemic effects observed at this dose level. (read-aross : 64742-53-6) (OECD TG 410, GLP)(ECHA)
  No systemic effects were observed. The NOAEL for lung changes associated with oil deposition in the lungs was 220 mg/m3. As no systemic toxicity was observed, the overall NOAEL for systemic effects was > 980 mg/m3. (read-aross : 64742-70-7) (OECD TG 412)(ECHA)
- Kerosine : oral; rat(male/female); 90 days; 750, 1500, or 3000 mg/kg/day(m), 325, 750, or 1500 mg/kg/day(f); The study LOAEL for systemic effects is 1500 mg/kg/day and the NOAEL for systemic effects is 750 mg/kg/day, based on reduced body weight in dams and in pups. (OECD TG 408, GLP) (read across: JP-8 jet fuel) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : oral; rat(male/female); No clinical signs of toxicity observed in either male or female rats. LD50 > 5000 ㎎/kg bw, no deaths (OECD TG 401, GLP) (read across: 64742-56-9) (ECHA)
  dermal; rabbit(male/female); No visible signs of clinical toxicity were observed in male and female rabbits dosed with API 78-9 at 5000 mg/kg. LD50 > 5000 ㎎/kg bw, no deaths (OECD TG 402, GLP) (read across: 64742-56-9) (ECHA)
  inhalation: aerosol; rat(male/female); The test material which was deposited on the animal fur during exposure diminished by observation Day 10. No mortality in either the control or exposed group was reported. There were no statistically significant differences in mean body weight between groups. LC50 > 5.53 mg/L air /4h, no deaths (OECD TG 403) (read across: MRD-87-102) (ECHA)

○ **Aspiration hazard : Not classified**

- Distillates (petroleum), hydrotreated heavy paraffinic : Viscosity: 73.9 mm2/s (40°C)(ECHA) & hydrocarbons
- Kerosine : 2.4 cSt at 40°C (ECHA) & hydrocarbons
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : 8.4 mm2/s (40°C) (ECHA) & hydrocarbons

12. ECOLOGICAL INFORMATION

1) Ecotoxicity

- Acute toxicity : Not classfied (ATEmix>1mg/L)
- Chronic toxicity : Not classfied

○ **Acute (short-term) aquatic hazard:**

Fish

- Distillates (petroleum), hydrotreated heavy paraffinic : 96h-LL50(Pimephales promelas) > 100 mg/L (OECD TG 203, GLP)(ECHA)
- Kerosine : No toxic effect observed within the range of water solubility(0.0037 mg/L). (EPISUITE) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : 96h-LL50(Pimephales promelas) > 100 mg/L (OECD TG 203, GLP) (ECHA)

Invertebrates

- Distillates (petroleum), hydrotreated heavy paraffinic : 48h-EL50(Daphnia magna) > 10,000 mg/L(read across : 64742-53-6 or 64741-97-5) (OECD TG 202)(ECHA)
- Kerosine : No toxic effect observed within the range of water solubility(0.0037 mg/L). (EPISUITE) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : 48h-EL50(Daphnia magna) > 10000 mg/L (OECD TG 202) (ECHA)

Aquatic algae

- Distillates (petroleum), hydrotreated heavy paraffinic : Not available
- Kerosine : No toxic effect observed within the range of water solubility(0.0037 mg/L). (EPISUITE) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not available

○ **Chronic (Long-term) aquatic hazard:**

Fish

- Distillates (petroleum), hydrotreated heavy paraffinic : Not available
- Kerosine : Not available
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not available

Invertebrates

- Distillates (petroleum), hydrotreated heavy paraffinic : 21d-NOEL(Daphnia magna)=10 mg/L(OECD TG 211, GLP)(ECHA)
- Kerosine : No toxic effect observed within the range of water solubility(0.0037 mg/L). (EPISUITE) (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : 21d-NOEL(Daphnia magna) = 10 mg/L (OECD TG 211, GLP) (ECHA)

Aquatic algae

- Distillates (petroleum), hydrotreated heavy paraffinic : 72h-NOErL(Pseudokirchnerella subcapitata) >= 100 mg/L (OECD TG 201) (ECHA)
- Kerosine : Not available
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : 72h-NOErL(Pseudokirchneriella subcapitata) >=100 mg/L (OECD TG 201) (ECHA)

2) Persistence and degradability

○ **Persistence**

- Distillates (petroleum), hydrotreated heavy paraffinic : This substance is UVCB, so not applicable.(ECHA)
- Kerosine : log Kow = 6.10 (exp.) (EPISUITE)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : log Kow = 6.13 (experimental) (EPISUITE)

○ **Degradability**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not available
- Kerosine : Not available
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not available

3) Bioaccumulative potential

○ **Bioaccumulation**

- Distillates (petroleum), hydrotreated heavy paraffinic : This substance is UVCB, so not applicable.(ECHA)
- Kerosine : BCF = 207.7 (estimated) (EPISUITE)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : BCF = 5147 (EPISUITE)

○ **Biodegradation**

- Distillates (petroleum), hydrotreated heavy paraffinic : 31% degradation after 28 days (OECD TG 301F) (read across: Solvent Neutral 600 Base Oil (MRD-94-981)) (OECD TG 301F, GLP)(ECHA)
- Kerosine : Kerosines are readily to inherently biodegradable. (ECHA)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : 31% degradation after 28 days; not readily biodegradable (OECD TG 301F, GLP) (ECHA)

4) Mobility in soil

- Distillates (petroleum), hydrotreated heavy paraffinic : Not available
- Kerosine : Koc = 196700 (EPISUITE)
- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Koc = 208800 (EPISUITE)

5) Hazard to the ozone layer

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

6) Other adverse effects

- Distillates (petroleum), hydrotreated heavy paraffinic : Not available
- Kerosine : Not available

- Polyisobutylene : Not available
- Trade secret : Not available
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not available

13. DISPOSAL CONSIDERATIONS

1) Disposal methods

- Not available

2) Special precaution for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

1) UN No.

- Not applicable

2) Proper shipping name

- Not applicable

3) Transport hazard class(es)

- Not applicable

4) Packing group

- Not applicable

5) Marine pollutant

- Not applicable

6) Special safety response for transportation or transportation measure

- Types of Emergency Measures in Case of Fire : Not applicable
- Types of Emergency Measures in Leakage : Not applicable
- Transport regulations according to ADR/RID, AND, IMDG and ICAO/IATA : Not applicable

15. REGULATORY INFORMATION

EINECS(or ELINCS)

- Distillates (petroleum), hydrotreated heavy paraffinic : European EINECS phase-in substance
- Kerosine : European EINECS phase-in substance
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : European EINECS phase-in substance

EU CLP (CLASSIFICATION) - PRODUCT : Not applicable

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

Substances restricted under REACH

- Distillates (petroleum), hydrotreated heavy paraffinic : Substances restricted under REACH
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Substances restricted under REACH

Substances subject to authorization under REACH

REACH SVHC List

Korea

○ **Occupational Safety and Health Act**

- Distillates (petroleum), hydrotreated heavy paraffinic : Substance subject to occupational exposure limits, Harmful agents subject to work environment monitoring, Harmful agents subject to workers requiring health examination
- Kerosine : Substance subject to occupational exposure limits, Substance subject to submission of process safety reports
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Substance subject to occupational exposure limits, Harmful agents subject to work environment monitoring, Harmful agents subject to workers requiring health examination

○ **K-REACH**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **Chemical Control Act in Korea**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **Safety Control of Dangerous Substances Act**

- Distillates (petroleum), hydrotreated heavy paraffinic : Dangerous substance
- Kerosine : Dangerous substance
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

U.S.A

○ **US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **CERCLA Designation of hazardous substances (40 CFR 302.4)**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **CERCLA Section 302 regulation**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **CERCLA Section 304 regulation**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **CERCLA Section 313 regulation**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

Interntional Convention on Environment

○ **Rotterdam Convention list**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **Stockholm Convention list**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **Montreal Protocol list**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

National Inventory

○ **Korea**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Not applicable
- Polyisobutylene : Not applicable
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

○ **U.S.A**

- Distillates (petroleum), hydrotreated heavy paraffinic : US TSCA phase-in substance
- Kerosine : US TSCA phase-in substance
- Polyisobutylene : US TSCA phase-in substance
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : US TSCA phase-in substance

○ **China**

- Distillates (petroleum), hydrotreated heavy paraffinic : China phase-in substance
- Kerosine : China phase-in substance
- Polyisobutylene : China phase-in substance
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : China phase-in substance

○ **Japan**

- Distillates (petroleum), hydrotreated heavy paraffinic : Not applicable
- Kerosine : Japan ENCS phase-in substance
- Polyisobutylene : Japan ENCS phase-in substance
- Trade secret : Not applicable
- Distillates (petroleum), solvent-dewaxed light paraffinic : Not applicable

16. OTHER INFORMATION

1) Reference

- Sources of information used in preparing this SDS included one or more of the following: Internal technical data, data from OECD eChemPortal, ECHA, NITE, TOXNET, IPCS and KOSHA search results.

2) Issue Date

- 2012-11-30

3) Revision number and Last date revised

○ **Number of revised**

- 6

○ **Date of last revision**

- 2024-06-24

○ **Last Revision History**

- Revision of chemical composition and company information

4) Other

- The information contained in the Safety Data Sheet is at the date of its issuance to the best of our knowledge correct according to the data available to us. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of

this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.